360 ° non angular design, soft touch Perfect combination of ergonomics and visual psychology Flat design, small–sized and exquisite Patent Code: 201930255520.0

Woson self-developped Steam Generator, blocking-free, upgrading efficiency by 10% the latest.

- Exclusive patent, Patent No.: ZL 201420135729.5
- · Greater thermal efficiency
- Longer service life



Sterilization Class Class B	Sterilization Temperature 121°C,134°C
Special Program HIV, HBV mad cow virus and spores	Dry Program Strong Vacuum Drying
Display 4.3 inch high-light LCD, touch screen	Test Program Bowie&Dick Test, Vacuum Test, Helix Test
Control Precision Temperature: 1°C , Pressure: 0.1bar	Sterilization Data External Printer, USB
Safety System Relief Valve, Motor Lock, Pressure and Temperature Overload Protection, Alarm System	Water Supply System Detachable reservoir Capacity: 7L
Rack & Trays 1 Tray	Chamber Medical Grade Aluminum Alloy, Max.temperature:145℃, Max.Working Pressure:2.3bar, Min.Working Pressure: –0.96bar

- * Chamber Material: Medical Grade Aluminum Alloy 6061
- * Lightweight and durable, excellent interface features, easy coating, high strength and strong corrosion resistance, commonly used in aircraft parts, ship accessories, precision instruments and other areas;
- * Split heating membranes in chamber, heating faster and more even;
- * Drawer-shape design, simple and easy operation.
- * Motor lock system, keep door shut during full cycle time, no matter positive or negative pressure.





Speedy sterilizing experience

Program	Temperature	Pressure	Vacuum Time	Sterilization Time	Dry Time	Total Time
N Class	134℃	210kPa	0	4mins	1mins	8mins
S Class	134℃	210kPa	1	4mins	3mins	12mins
B Class 134°C	134℃	210kPa	3	4mins	4mins	15mins
B Class 121 ℃	121℃	110kPa	3	20mins	4mins	30mins

SPECIFICATION

Model	Voltage/Power	Chamber Size(mm)	Outside Size(mm)	Packing Size(mm)	Net Weight(kg)
TANCY TOUCH 2L	220V/1800W	192.5X45.5X300	620X440X170	750X520X230	27

TANCY TOUCH provides superior faster performance than existing rivals.

